# Side doors

A matching side door for every garage door



Hörmann offers matching side doors for all of its garage doors. On request in the exact same alignment as your sectional garage door.

The perfect addition: a side door to match your garage door

# Ready-to-fit door set

Hörmann side doors are supplied ready-to-fit with profile cylinder mortise lock, round handle / lever handle set with oval rose escutcheons and on models with block frame with 3-way adjustable hinges. Door leaf frames are made of weather-proof aluminium extrusions (depth 60 mm) with all-round seals.

Side doors are available in the surface finishes: Woodgrain, Silkgrain, Micrograin, Decograin Titan Metallic and Decograin timber decors. We offer timber doors in Nordic Pine and Hemlock.





Lever handle set

Choose between the standard plastic lever handle in black or optional lever handle or lever / knob handle set in many other materials (Fig: stainless steel lever handle set).

#### Matching

Decograin side doors with block frames or corner frames come with identical surfaces for the frame, subframe and door to create a matching appearance.

	_	
		1
a;		
_		

### Narrow surround

Depending on the height of the door, variable handle position between 898 and 1064 mm from FFL.

Aluminium block frame (profile type 1) for fitting behind the opening or in the opening (opening inwards)

Aluminium corner frame (profile type 1) for internal fitting

Aluminium corner frame (profile type 3) for external fitting

		-
- 12		
		π.
-		
		-
-		-
-		-
1.0		-
-		-
41		
10		2
7	-	ł
1		1
đ		1
1	-	
	-	
	-	
	-	
	-	
	-	
	-	
	-	

## **Broad surround**

Lever height set at 1050 mm from FFL

Aluminium block frame (profile type 2) for fitting behind the opening or in the opening (opening inwards or outwards)

Aluminium corner frame (profile type 2) for internal or external fitting

For further information, please see the fitting data or contact your Hörmann partner.

Break-in-resistant

3-point locking as optional equipment for profile type 2 with latch, bolt, 2 locking hooks and security rose escutcheon class 2 according to DIN V EN V 1627-1630.

# Dimensions and fitting data

Steel side doors

### Standard sizes, steel side doors

Ordering size	Structural opening	Lever height		
		P1	P2	P3

Block frame, fitting behind the opening (ordering size = overall frame dimension) P1 (only opening inwards) and P2

990 × 2058	855 - 875 × 1990 - 2000	955	1050	
990 × 2183	855 - 875 × 2115 - 2125	1010	1050	
1115 × 2058	980 - 1000 × 1990 - 2000	955	1050	
1115 × 2183	980 - 1000 × 2115 - 2125	1010	1050	

#### Block frame, fitting in the opening (ordering size = overall frame dimension) P2 (only S, M, L ribbed)

855 × 1990	875 ×2000	1050	
855 × 2115	875 × 2125	1050	
980 × 1990	1000 × 2000	1050	
980 × 2115	1000 × 2125	1050	


Corner frame, internal fitting (ordering size = nominal size) P1 and P2 (only S, M, L ribbed)

875 × 2000	955	1050	
875 × 2125	1010	1050	
1000 × 2000	955	1050	
1000 × 2125	1010	1050	


Corner frame, external fitting (ordering size = nominal size) P2 (only S, M, L ribbed) and P3

875 × 2000	1050	955
875 × 2125	1050	1010
1000 × 2000	1050	955
1000 × 2125	1050	1010


### Vertical view



Side door with aluminium block frame, profile type 2 fitting behind the opening




Side door with aluminium block frame, profile type 2 fitting in the opening




Side door with aluminium corner frame, profile type 2 external fitting


### Horizontal view



Side door with aluminium block frame, profile type 1 fitting behind the opening



Side door with aluminium block frame, profile type 2 fitting behind the opening



Side door with aluminium corner frame, profile type 3 external fitting