



# Aluminium entrance doors

For elegant entrances in a safe and beautiful home

**HÖRMANN**









## CONTENT

- 4 Programme overview
- 6 Design overview
- 8 Good reasons to try Hörmann
- 14 Security equipment
- 17 ThermoSafe, ThermoSafe Hybrid
- 49 ThermoPlan Hybrid
- 61 ThermoCarbon
- 75 TopComfort
- 81 Special equipment
- 90 Lock variants ThermoSafe, ThermoSafe Hybrid  
ThermoPlan Hybrid, ThermoCarbon
- 99 Hörmann product range

The colours and surface finishes shown are subject to the limitations of the printing process and cannot be regarded as binding.

Some of the products and equipment details described and illustrated in this catalogue are not standard, but available for a surcharge. Descriptions and pictures, information about the scope of delivery, equipment and colour correspond to the time of printing. Subject to changes and errors.

All rights reserved. No part may be reproduced without our prior permission.

◀ **ThermoSafe style 860** in the standard colour Traffic white RAL 9016, matt, with side elements

# Hörmann brand quality impresses in every version

Hörmann aluminium entrance doors are superior to plastic or timber doors in many ways. These benefits will convince you:

- High thermal insulation
- High security
- High acoustic insulation
- Great stability
- No follow-up painting necessary

Hörmann entrance doors look new even after many years, and also offer you a large variety of options with regard to technical equipment and design. Five entrance door versions from Europe's no. 1 are available for you to choose from. Discover your new entrance door!





#### Exclusive class: ThermoSafe

Our best-selling aluminium entrance doors ThermoSafe are characterised by a **large selection of styles**.

---

Learn more about our ThermoSafe doors from page 17

---

#### Top class: ThermoSafe Hybrid

ThermoSafe Hybrid entrance doors ensure particularly high leaf rigidity and dimensional stability thanks to the stainless steel sheet on the door leaf exterior.

---

Learn more about our ThermoSafe Hybrid doors from page 17

---



#### Design class: ThermoPlan Hybrid

The ThermoPlan Hybrid door combines the benefits of stainless steel and aluminium for a special door view thanks to a flush transition between the frame and door leaf.

---

Learn more about our ThermoPlan Hybrid doors from page 49

---



#### Premium class: ThermoCarbon

The thermal insulation world champion among aluminium entrance doors is characterised by a 100-mm-thick door leaf with a high-tech leaf profile made of carbon glass-fibre.

---

Further advantages of the ThermoCarbon doors can be found from page 61

---



#### Comfort class: TopComfort

This entrance door complies with all your demands for maximum light thanks to its extensive glazing.

---

Discover all the possibilities from page 75

---



#### Top class: Thermo65

Thanks to standard multiple-point locking, these inexpensive entrance doors give you a feeling of security, save energy through excellent thermal insulation and provide a stylish appearance for your home.



More information can be found in the "Entrance doors Thermo65 / Thermo46" brochure.

\* Recommended retail price incl. 16 % VAT

ThermoSafe / ThermoSafe Hybrid





## ThermoPlan Hybrid

## ThermoCarbon

## TopComfort



Style 138  
Page 53



Style 189  
Page 53



Style 501  
Page 54



Style 189  
Page 65



Style 300  
Page 66



Style 301  
Page 66



Style 302  
Page 68



Style 100  
Page 78



Style 101  
Page 78



Style 502  
Page 54



Style 503  
Page 53



Style 504  
Page 54



Style 304  
Page 71



Style 305  
Page 71



Style 306  
Page 68



Style 308  
Page 71



Style 100  
MG 111  
Page 78



Style 100  
MG 112  
Page 78



Style 505  
Page 54



Style 686  
Page 53



Style 823  
Page 55  
■ NEW



Style 309  
Page 71



Style 310  
Page 68



Style 312  
Page 68



Style 314  
Page 68



Style 100  
MG 113  
Page 79



Style 100  
MG 114  
Page 79



Style 860  
Page 53



Style 862  
Page 56



Style 867  
Page 56



Style 504  
Page 65



Style 565  
Page 66



Style 568  
Page 66



Style 650  
Page 65



Style 100  
MG 115  
Page 79



Style 100  
MG 116  
Page 79



Style 871  
Page 56



Style 872  
Page 56



Style 680  
Page 65



Style 686  
Page 65



Style 823  
Page 69  
■ NEW



Style 860  
Page 70



Style 100  
MG 117  
Page 79



Style 862  
Page 65

## Configurator

With the door configurator, you can conveniently test many design and product variations on your own PC or tablet in advance. You can put together your dream door in just a few clicks by selecting the door programme, style, colour and size.



The Hörmann configurator can be found on our website.

“A good reputation must be earned.”

August Hörmann


In keeping with the tradition started by the company's founder, the name Hörmann delivers brand name quality with extensive product expertise. The family business has over 80 years of experience as a construction component specialist and sees itself as your partner from the very beginning of building and renovation projects. It's no surprise that Hörmann is one of Europe's most successful entrance door providers. All of this gives you a good feeling when you purchase a Hörmann entrance door.



## 1 Made in Germany

All doors are developed and manufactured by Hörmann. Our highly qualified employees work intensively on new products, continual further developments and improvements to details. The results are patents and unique products on the market. Endurance tests under real conditions **ensure mature series products with Hörmann quality.**






## 2 Quality products for generations

We are convinced of our products and our uncompromising quality assurance. That is why we at Hörmann issue a **10-year guarantee\*** on **ThermoSafe, ThermoSafe Hybrid, ThermoPlan Hybrid, ThermoCarbon and TopComfort entrance doors.**

## 3 An eye on the future

Hörmann is setting a good example. This is why the company obtains **100 % of its energy consumption from green sources.** Together with an intelligent and certified energy management system, CO<sub>2</sub>-neutral mailing and the recycling of valuable materials, more than **40000 tons of CO<sub>2</sub> are saved each year.** And last but not least, Hörmann also offers products for sustainable construction.

\* The complete warranty conditions can be found at:  
[www.hoermann.com](http://www.hoermann.com)



## 4 Fully foamed door leaf construction



**Only from Hörmann**

No thermal bridges for glazings

For ThermoSafe, ThermoSafe Hybrid, ThermoPlan Hybrid and ThermoCarbon entrance doors, the entire door leaf is delivered fully foamed. This way, the PU foam is optimally bonded to the door profile **1**, the internal and external sheets **2** and the glazing **3**. In contrast to other door systems, where the components are only glued together, this construction is characterised by a particularly high dimensional stability and break-in resistance as well as even better thermal insulation, as no thermal bridges are created.





Exterior view



Interior view

## 5 Door leaf without visible leaf profile



Our ThermoSafe, ThermoSafe Hybrid, ThermoPlan Hybrid and ThermoCarbon entrance doors give you an exquisite and elegant reception. The shapely **door leaf with its solid interior and exterior** and leaf profile on the inside fulfils the highest design requirements. The interior view harmonises perfectly with your residential internal doors.



External view of entrance doors from other manufacturers with visible leaf profile



Interior view of entrance doors from other manufacturers with visible leaf profile and glazing beads



## 6 Excellent thermal insulation

**ThermoCarbon aluminium entrance doors with a  $U_D$ -value of up to approx.  $0.47 \text{ W}/(\text{m}^2 \cdot \text{K})^*$**

Our doors are the new generation of high-insulation entrance doors. With  $U_D$ -values up to approx.  $0.78 \text{ W}/(\text{m}^2 \cdot \text{K})$ , ThermoPlan Hybrid doors have excellent thermal insulation values. ThermoSafe Hybrid and ThermoSafe entrance doors are also distinguished by their  $U_D$ -values of up to approx.  $0.87 \text{ W}/(\text{m}^2 \cdot \text{K})$ . All door systems comply with all the requirements of the energy saving regulation. **Our ThermoCarbon entrance doors are clearly the world champions when it comes to thermal insulation: They feature unparalleled  $U_D$ -values up to  $0.47 \text{ W}/(\text{m}^2 \cdot \text{K})$  and are also certified for low-energy houses by the ift Rosenheim.**

## 7 Flush transition

With the aluminium and stainless steel materials used on the ThermoPlan Hybrid entrance doors, you can enjoy an elegant, flush door view. **You will not be able to see and feel any offset on the inside and outside between the door leaf and door frame.** Due to the stainless steel sheet on the outside, particularly high leaf rigidity is guaranteed.





## 8 Safe glazing



8 mm laminated safety glass on the interior and exterior as standard

When it comes to **industrial safety and burglar protection**, Hörmann entrance doors fulfil the absolute highest demands. The laminated safety glass on the interior and exterior of the triple-pane insulated glazing provides **maximum security**. In case of glass breakage, the glass splinters are also bound on the inside, **virtually eliminating any danger of being injured by the shards**. Furthermore, the laminated safety glass offers better protection against burglars as it makes reaching through more difficult.

## 9 Barrier-free entrances

The Hörmann **ECturn opening aid** makes **it easier for you to open** your ThermoSafe, ThermoSafe Hybrid, ThermoPlan Hybrid and ThermoCarbon entrance door. Due to low energy operation, the opening aid requires no safety devices. **Door operator HDO 200 opens and closes your TopComfort entrance door fully automatically**. For your security, the Flatscan sensor monitors the inside and outside of the door. Both systems can be conveniently operated with Hörmann BiSecur hand transmitters or radio buttons. For further information, see page 93.

## We protect you from unwanted visitors

An apartment is broken into every three minutes, making it even more important to equip your entrance door with a high security standard. If a burglar is not successful within approx. 90 seconds, they generally give up their break-in attempt. For this reason, nearly half of all break-in attempts fail if the entrance door is break-in-resistant. The carefully tested burglar protection is also recommended by police information centres. Further information can be found at: [www.k-einbruch.de](http://www.k-einbruch.de)



## 10 Security equipment as standard

Our entrance doors make it especially difficult for burglars to break into your home. This protects your home from break-in attempts. Additionally, the security features are not visible on the door, unlike with many competitor solutions. That's brand quality from Hörmann!



Security equipment	RC 4	RC 3	RC 2
ThermoSafe		●	
ThermoSafe Hybrid	●*	●**	
ThermoPlan Hybrid		●	
ThermoCarbon	○	●	
TopComfort		○	○
Side element / transom light		○	○

● = As standard ○ = Optional  
 \* Door styles without glazing  
 \*\* Door styles with glazing




# 11 Security promise


In the unlikely event of a break-in through a ThermoSafe, ThermoSafe Hybrid, ThermoPlan Hybrid or ThermoCarbon entrance door with RC 3 or RC 4 security equipment, Hörmann can provide

**a new Hörmann entrance door with the same equipment, including specialist fitting by a Hörmann partner**

or

**£3000 in cash (e.g. if the damage is covered by your household insurance)**

 You can find further information and a video on the topic at [www.hoermann.de/](http://www.hoermann.de/)

 **sicherheitsversprechen**




The experienced burglar attempts to break open the locked door with simple tools, e.g. a crowbar, as well as simple striking tools within 10 minutes.



The burglar attempts to break open the locked door with simple tools, e.g. a crowbar, as well as simple drilling tools within 5 minutes.



The opportunist burglar attempts to break open the locked door with simple tools within 3 minutes.







## The perfect balance between comfort and security

Our ThermoSafe and ThermoSafe Hybrid entrance doors will convince you with their security and thermal insulation. Thanks to a  $U_D$ -value of up to  $0.87 \text{ W}/(\text{m}^2 \cdot \text{K})$ , the doors keep the cold out and the standard security equipment gives you a feeling of safety when you go to bed at night. The aluminium stainless steel entrance door ThermoSafe Hybrid impresses with its high dimensional stability and leaf rigidity, even with large temperature fluctuations inside and outside.

More than 70 door styles, 19 preferred colours, optional handle variants, glazings and operators are available to choose. The result: your individual dream door!



## Construction

- 1 Solid 73 mm aluminium door leaf with PU rigid foam infill and internal leaf profile
- 2 Aluminium leaf profile with thermal break
- 3 82 mm aluminium door frame with thermal break
- 4 Triple sealing with an all-round seal

Fulfils all requirements of the energy saving regulation

Suitable for fitting without thermal bridges

**Thermal insulation:**

$U_D$ -value of up to approx.  $0.87 \text{ W}/(\text{m}^2 \cdot \text{K})^*$

**Acoustic insulation:**  $R_{w,p}$  up to 34 dB (ThermoSafe), 36 dB (ThermoSafe Hybrid)

The complete performance characteristics can be found on page 94.

## ThermoSafe



As standard for ThermoSafe

RC 3 security equipment as standard\*\*

## ThermoSafe Hybrid



- 5 Particularly high leaf rigidity and added security due to exterior stainless steel sheet

RC 4 security equipment\*\* as standard and H5 security lock (styles without glazing)


RC 3 security equipment as standard\*\* (styles with glazing)



As standard for doors without glazing



As standard for doors with glazing





## Equipment

- 6 Solid door view from the inside, as standard in Traffic white RAL 9016, matt, like on residential internal doors
- 7 Flush-fitting transition from the door leaf to the door frame on the inside
- 8 3-way adjustable hinges
- 9 Aluminium interior lever
- 10 Triple-pane thermal insulation glazing with safety glass on both sides
- 11 Profile cylinder protected against manipulation
- 12 With 5-point security lock
- 13 Security bolts

## Colour

- As standard in Traffic white, RAL 9016, matt
- Optionally in 19 preferred colours
- Optionally in RAL to choose

For further information, see page 84.

## Interior view



\* Dependent on door size. Specified values for RAM 1230 x 2180 mm

\*\* Break-in-resistant components are only effective in preventing burglaries when closed and locked, with the key removed.





**Style 75**

Standard colour Traffic white RAL 9016, matt, stainless steel handle 38-1, Master-Carré ornamental glass




**Style 65**

Preferred colour Hörmann CH 607 Chestnut, fine structure, matt, stainless steel handle HOE 600, matt float design glass with 7 clear stripes



**Style 185**

Standard colour Traffic white RAL 9016, matt, stainless steel handle 38-2, Master-Carré white ornamental glass



**Style 45**


Preferred colour Hörmann CH 703 Anthracite, fine structure, matt, stainless steel handle HOE 200, matt Parsol grey design glass with 4 clear stripes

◀ **ThermoSafe style 75**

in standard colour Traffic white RAL 9016, matt, with side element



An invitation to feel at home



**Style 680**

Standard colour Traffic white RAL 9016, matt, stainless steel handle HOE 700, Pave white ornamental glass



**Style 110**

Preferred colour Stone grey RAL 7030, matt, stainless steel handle 38-1, optional Cathedral white ornamental glass



**Style 138 ■ NEW**

Standard colour Traffic white RAL 9016, matt, stainless steel handle HOE 500, Satinato ornamental glass



**Style 650**

Preferred colour Window grey RAL 7040, matt, stainless steel handle HOE 700, Pave white ornamental glass



**Style 140**

Preferred colour Slate grey RAL 7015, matt, stainless steel handle 38-1, stainless steel embellishment, Pave white ornamental glass








**Style 501**

Preferred colour Quartz grey RAL 7039, fine structure matt, stainless steel handle HOE 500, Satinato glazing



**Style 502**

Standard colour Traffic white RAL 9016, matt, stainless steel handle HOE 500, Satinato glazing



**Style 505**

Standard colour Traffic white RAL 9016, matt, stainless steel handle HOE 500, matt float design glass with 4 clear stripes



**Style 504**

Preferred colour Slate grey RAL 7015, fine structure matt, stainless steel handle HOE 500, matt float design glass with 7 clear stripes

◀ **ThermoSafe style 504**

in preferred colour Grey aluminium RAL 9007, fine structure matt




**Style 686**

Preferred colour Ruby red RAL 3003, matt, stainless steel handle HOE 600, stainless steel embellishment, matt float design glass with 7 clear stripes



**Style 860**

Standard colour Traffic white RAL 9016, matt, stainless steel handle HOE 700



**Style 503**

Preferred colour Cream RAL 9001, fine structure matt, stainless steel handle HOE 500, matt float design glass with 7 clear stripes



**Style 189**

Standard colour Traffic white RAL 9016, matt, stainless steel handle HOE 615, matt float design glass with 7 clear stripes



**Style 867**

Standard colour Traffic white RAL 9016, matt, stainless steel handle HOE 620, matt float design glass with 7 clear stripes



**Style 871**

Preferred colour Slate grey RAL 7015, fine structure matt, stainless steel handle HOE 620, side elements with matt float design glass with 3 clear stripes



**Style 862**

Preferred colour Quartz grey RAL 7039, fine structure matt, stainless steel handle HOE 620



**Style 872**

Standard colour Traffic white RAL 9016, matt, stainless steel handle HOE 615, side elements with matt float design glass with 6 clear stripes





## Impressive extras for design enthusiasts: LED spotlights



### Style 723

Preferred colour Grey aluminium RAL 9007, fine structure matt, with optional LED spotlight in handle, handle profile in White aluminium RAL 9006, fixing profiles in door colour, ornamental glass Satinato



### Style 823

Preferred colour Grey aluminium RAL 9007, fine structure matt, with optional LED spotlight in handle, handle profile in White aluminium RAL 9006, fixing profiles in door colour, optional fascia frame Caro

◀ **Style 823** in preferred colour Anthracite grey RAL 7016, fine structure matt, optionally with LED spotlight in handle, handle profile in White aluminium RAL 9006, fixing profiles in door colour, with side element



**Style 565**

Preferred colour Stone grey RAL 7030, fine structure matt, with handle embellishment in DecoGrain Golden Oak, side elements with ornamental glass matt float



**Style 832**

Standard colour Traffic white RAL 9016, matt, stainless steel handle HOE 820, embellishment in Slate grey RAL 7015, with horizontal and vertical stainless steel pilaster strips



**Style 568**

Preferred colour Hörmann CH 703 Anthracite, fine structure matt, side elements with matt float ornamental glass, design handle G 750, optionally also with light strip integrated in the handle



**Style 836**

Standard colour Traffic white RAL 9016, matt, stainless steel handle HOE 820, flush-fitting embellishment in Slate grey RAL 7015





**Style 693**

White aluminium, RAL 9006, silk-gloss,  
stainless steel handle HOE 300



**Style 891\***

Preferred colour Quartz grey  
RAL 7039, fine structure matt,  
security handle set 62-1



**Style 689**

Standard colour Traffic white RAL 9016, matt,  
stainless steel handle 38-2, matt Parsol grey  
design glass with 7 clear stripes



**Style 861**

Standard colour Traffic white  
RAL 9016, matt,  
stainless steel handle HOE 700







**Style 514**

Standard colour Traffic white RAL 9016, matt, design handle G 750 in White aluminium RAL 9006, silk-gloss, clear float glazing



**Style 524**

Preferred colour Anthracite grey RAL 7016, fine structure matt, design handle G 750 in White aluminium RAL 9006, silk-gloss, clear float glazing



**Style 877**

Standard colour Traffic white RAL 9016, matt, stainless steel handle HOE 610, matt float design glass with 3 clear stripes



**Style 879**

Standard colour Traffic white RAL 9016, matt, design handle G 750 in anodised aluminium E6 / EV 1, matt float design glass with 3 clear stripes





**Style 759**

Standard colour Traffic white RAL 9016, matt, design handle G 750 in anodised aluminium E6 / EV 1, matt float design glass with clear stripes



**Style 757**

Preferred colour Grey aluminium RAL 9007, fine structure matt, stainless steel handle HOE 797, matt float design glass with clear stripes



**Style 777**

Standard colour Traffic white RAL 9016, matt, stainless steel handle HOE 610, matt float ornamental glass



**Style 779**

Preferred colour Stone grey RAL 7030, fine structure matt, design handle G 750 in anodised aluminium E6 / EV 1, matt float ornamental glass, side elements with matt float ornamental glass with 5 clear stripes








**Style 176**

Preferred colour White aluminium, RAL 9006, silk-gloss, stainless steel handle HOE 735, Satinato ornamental glass



**Style 177**

Standard colour Traffic white RAL 9016, matt, stainless steel handle HOE 700, Pave white ornamental glass



**Style 799**

Standard colour Traffic white RAL 9016, matt, design handle G 750 in anodised aluminium E6 / EV 1, matt float ornamental glass, side elements with matt float design glass with 6 clear stripes



**Style 797**


Preferred colour Anthracite grey RAL 7016, fine structure matt, stainless steel handle HOE 797, matt float ornamental glass

◀ **ThermoSafe style 177** in preferred colour Slate grey RAL 7015, matt



**Style 136**

Standard colour Traffic white RAL 9016, matt, stainless steel handle 38-1, Satinato design glass with 7 matt stripes



**Style 560**

Standard colour Traffic white RAL 9016, matt, stainless steel handle HOE 600, matt design glass with 11 clear stripes



**Style 166**

Preferred colour Hörmann CH 703 Anthracite, fine structure, matt, stainless steel handle 38-1, stainless steel embellishment, Satinato design glass with 7 matt stripes



**Style 697**

Preferred colour Hörmann CH 703 Anthracite, fine structure, matt, with Rondo 70 fascia frame, stainless steel handle HOE 910, matt Parsol grey design glass with 7 clear stripes



**Style 40**

Preferred colour Stone grey RAL 7030, fine structure matt, stainless steel handle HOE 550, design glass partially matt



**Style 551**

Standard colour Traffic white RAL 9016, matt, hand-crafted stainless steel handle HOE 150, with fascia frame Rondo 70



**Style 552**

Standard colour Traffic white RAL 9016, matt, hand-crafted stainless steel handle HOE 150, matt float design glass with clear stripes and red colour stripes



**Style 553\***

Standard colour Traffic white RAL 9016, matt, aluminium handle G 753 in silver, matt Reflo design glass with genuine fluted glass



**Style 590\***

Preferred colour Slate grey RAL 7015, matt, colour embellishment in Traffic white RAL 9016, matt, design handle G 750, Reflo design glass with genuine fluted glass and sandblasted design, with fascia frame Caro 70



**Style 583**

Preferred colour Anthracite grey, RAL 7016, matt, colour embellishment in Black brown RAL 8022, matt, aluminium handle G 755, matt Reflo design glass with clear edge

\* Not available as ThermoSafe Hybrid  
01933 229135









**Style 445**

Preferred Hörmann colour CH 607 Chestnut, fine structure matt, with design side elements, optional stainless steel handle 14-2, ornamental glass Chinchilla



**Style 402**

Standard colour + Traffic white RAL 9016, matt, stainless steel handle 14-2, Reflo design glass, partially matt with genuine fluted glass



**Style 413**

Standard colour Traffic white RAL 9016, matt, stainless steel handle 14-2, Silk ornamental glass



**Style 675**

Standard colour Traffic white RAL 9016, matt, with Rondo 70 fascia frame, stainless steel handle 38-1, Reflo design glass with genuine fluted glass



**Style 694**

Preferred colour Terra brown RAL 8028, matt, stainless steel handle HOE 700, Reflo design glass with genuine fluted glass

◀ Style 445 in standard colour Traffic white RAL 9016, matt, with optional Reflo glass with fluted glass and handle 38-1



# Perfectly matching entrance door and garage door

The extensive Hörmann programme with matching products provides you with aligned entrance door and garage door ribbing options for a matching appearance. The result: no offset from the base line. You will see: the beauty of your home is reflected in these small but crucial details.



## Perfectly matched: entrance door styles and sectional garage doors, M- or L-ribbed



**ThermoSafe entrance doors:**

- Style 825
- Style 845
- Style 855




**Sectional garage doors, M-ribbed:**

- with a door height of 2000 mm
- with a door height of 2125 mm
- with a door height of 2250 mm



**ThermoSafe entrance doors:**

- Style 875
- Style 895
- Style 898



**Sectional garage doors, L-ribbed:**

- with a door height of 2000 mm
- with a door height of 2125 mm
- with a door height of 2250 mm



▲ **ThermoSafe style 895** in preferred colour Anthracite grey RAL 7016, matt, with side element, L-ribbed sectional garage door in Silkgrain Anthracite grey RAL 7016

### Matching entrance and garage door

The cross-section of the entrance and garage door clearly shows: The ribbed look of the entrance door is due to the grooves in the infill. With the garage door, this is created by the ribbing of the individual sections and the section transitions. The aligned appearance also applies if the entrance door has a different installation height than the garage door. We can adjust the groove heights individually according to your specifications, all we need is the height offset.

After precise measurement on site, your Hörmann specialist dealer will advise you on the ideal overall look based on these entrance door styles.



ThermoSafe entrance door cross-section



Sectional garage door cross-section






# Matching entrance and garage doors\*



**Style 188**  
Preferred colour Anthracite grey RAL 7016, stainless steel handle HOE 100, matt float design glass with 3 clear stripes



**Sectional garage door**  
L-ribbed design style 457 in Silkgrain Anthracite grey RAL 7016



**Style 173**  
Preferred colour Ruby red RAL 3003, matt, stainless steel handle HOE 300, optional matt float ornamental glass, side elements with optional matt float design glass with 3 clear stripes



**Sectional garage door**  
L-ribbed design style 461 in Silkgrain Ruby red RAL 3003

◀ **Style 188** in standard colour Traffic white RAL 9016, matt, with side elements, sectional garage door, L-ribbed, design style 457 in Silkgrain Traffic white RAL 9016

\* The spacings between the entrance and garage door are not completely flush

# High quality all-round

## 1 3-way adjustable hinges

With the elegant, three-way adjustable hinges, the door leaf can be simply and conveniently adjusted by the Hörmann specialist partner. This way, your entrance door is optimally sealed and falls shut smoothly and securely.

## 2 Optional concealed hinges\*

Concealed hinges make for an elegant door appearance on the interior. The hinges feature leverage protection so that the security bolts on the hinge side can be omitted.

## 3 Tamper-proof profile cylinder

The profile cylinder is equipped with an anti-picking system, which prevents manipulation by objects inserted into the lock, and also has drill-proofing. In addition, it offers an emergency and hazard function, i.e. the door can still be opened and closed when a key is inserted on the inside. The tamper-proof locking cylinder is certified according to DIN 18252 / DIN EN 1303 and is delivered with 5 reversible keys and 2 key caps.

## Exterior surface-mounted security rose escutcheon


The patented exterior rose escutcheon also protects the profile cylinder against being drilled open and twisted off. Delivered as standard in Traffic white RAL 9016, or in stainless steel for coloured doors.

## 4 Aluminium interior lever

ThermoSafe Hybrid and ThermoSafe entrance doors are equipped as standard with the attractive interior lever Rondo, stove-enamelled in white. Optionally, it is also available in stainless steel or RAL to choose as well as in versions Caro or Okto, each in stainless steel.

## 5 Stainless steel lock plate

The lock plate is optimally adjusted by the Hörmann specialist partner so that your door falls shut optimally and can be securely locked.



**6 5-point security lock H5 and security bolts on the hinge side**

When locking, 3 steel swing bolts with 2 additional bolt locks pivot into the stainless steel lock plate. The swing bolts make it more difficult for the door to be pulled apart or forced open.

**7 Electronic spyhole (optional)**

Your entrance area is monitored with a wide angle camera. The spyhole with 3.5" LCD monitor is ideal for small children and persons who depend on a wheelchair.

**Integrated overhead door closer (optional, not shown)**

The integrated overhead door closer closes the door and gives it an elegant interior view – especially in combination with concealed hinges.

**Opening limiter\***  
(optional, not shown)

The high-quality opening limiter in the metal version restricts the door opening to an opening angle of 105°. It is individually adjustable and features the convenient soft stop function.

**8 Retractable bottom seal with weather protection**

Optional for all ThermoSafe and ThermoSafe Hybrid entrance doors: The retractable bottom seal is the best solution for barrier-free entrances without threshold. The sealing of the door bottom edge withstands driving rain and convinces with low air permeability.



Barrier-free entrances


## Optional frame variants

**9 Broader door frames**

On request, door frames are also available in a width of 110 mm, for a more convenient and attractive connection and full thermal insulation, for example.

**10 Fascia frame Caro 70**

This version has an attractive and distinguished look that adds value to your door through the spatial depth of the frame.



\* For doors opening inwards



## Elegance for your home

If you have high demands on security, thermal insulation and technical equipment, and also appreciate an exclusive look for your home, the ThermoPlan Hybrid is the right choice for you. The design of this door impresses with the flush transition between the frame and door leaf. The stainless steel sheet on the outside guarantees particularly high dimensional stability, even in case of large temperature differences.

In addition, the high-quality equipment appeals with  $U_D$ -values of up to approx.  $0.78 \text{ W}/(\text{m}^2 \cdot \text{K})$  and with RC 3 equipment as standard.

The ThermoPlan Hybrid entrance door is available in 12 elegant door styles and 19 preferred colours for you to choose from. With many other equipment options such as handles, glazing and lock variants, the ThermoPlan Hybrid becomes your individual dream door.

---

ThermoPlan Hybrid  
from €3900\*

---



# Construction

- 1** 82 mm aluminium door leaf with PU rigid foam infill and internal leaf profile
- 2** Flush-fitting transition from the door leaf to the door frame on the outside
- 3** High leaf rigidity due to painted exterior stainless steel sheet
- 4** Aluminium leaf profile with thermal break
- 5** 82 mm aluminium door frame with thermal break
- 6** Triple sealing with two all-round seals



Fulfills all requirements of the energy saving regulation and is suitable for low-energy houses

Suitable for fitting without thermal bridges

**Thermal insulation:  $U_D$ -value of up to approx.  $0.78 \text{ W}/(\text{m}^2 \cdot \text{K})^*$**

**Acoustic insulation:  $R_{w,p}$  up to 36 dB**

The complete performance characteristics can be found on page 94.



## Equipment

- 6 Solid door view from the inside, as standard in Traffic white RAL 9016, matt, like on residential internal doors
  - 7 Flush-fitting transition from the door leaf to the door frame on the inside
  - 8 3-way adjustable hinges
  - 9 Aluminium lever handle
  - 10 Triple-pane thermal insulation glazing with safety glass on both sides
  - 11 Profile cylinder protected against manipulation
- 
- 12 RC 3 security equipment\*\* with 5-point security lock
- 
- 13 Security bolts

## Colour

- As standard in Traffic white, RAL 9016, matt
- Optionally in 19 preferred colours
- Optionally in RAL to choose

For further information, see page 84.

## Interior view



\* Dependent on door size. Specified values for RAM 1230 x 2180 mm

\*\* Break-in-resistant components are only effective in preventing burglaries when closed and locked, with the key removed.





**Style 860**

Preferred colour Hörmann CH 703 Anthracite, fine structure matt, stainless steel handle HOE 700



**Style 189**

Preferred colour Light grey RAL 7035, matt, stainless steel handle HOE 615, matt float design glass with 7 clear stripes



**Style 138**

Standard colour Traffic white RAL 9016, matt, stainless steel handle HOE 500, Satinato ornamental glass



**Style 686**

Standard colour Traffic white RAL 9016, matt, stainless steel handle HOE 600, stainless steel embellishment, matt float design glass with 7 clear stripes, side elements with matt float design glass with 7 clear stripes



**Style 503**


Preferred colour White aluminium RAL 9006, silk-gloss, stainless steel handle HOE 500, matt float design glass with 7 clear stripes





**Style 501**

Preferred colour Fir green RAL 6009, matt, stainless steel handle HOE 500, Satinato glazing



**Style 504**

Standard colour Traffic white RAL 9016, matt, stainless steel handle HOE 500, matt float design glass with 5 clear stripes, side elements with matt float design glass with 7 clear stripes



**Style 502**

Standard colour Traffic white RAL 9016, matt, stainless steel handle HOE 500, Satinato glazing



**Style 505**

Standard colour Stone grey RAL 7030, matt, stainless steel handle HOE 500, matt float design glass with 4 clear stripes, side elements with matt float design glass with 4 clear stripes

For the highest demands



**Style 823 ■ NEW**

Standard colour Traffic white RAL 9016, matt, handle profile in White aluminium RAL 9006, fixing profiles in door colour



**Style 872**

Preferred colour Anthracite grey  
RAL 7016, matt, stainless steel  
handle HOE 615



**Style 871**

Standard colour Traffic white RAL 9016, matt, stainless steel handle  
HOE 620, side elements with matt float design glass with 3 clear stripes



**Style 862**

Standard colour Traffic white  
RAL 9016, matt, stainless steel  
handle HOE 620



**Style 867**

Preferred colour Quartz grey RAL 7039, matt, stainless steel handle  
HOE 620, matt float design glass with 7 clear stripes, side elements  
with matt float design glass with 7 clear stripes





# High quality all-round

## 1 3-way adjustable hinges

With the elegant, three-way adjustable hinges, the Hörmann specialist partner can very easily succeed in optimally adjusting the ThermoPlan Hybrid entrance door. This way, your entrance door is optimally sealed and always falls smoothly and securely into its lock.

## 2 Optional concealed hinges

Concealed hinges make for an elegant door appearance on the interior. Thanks to hinge leverage protection, security bolts on the hinge side can be omitted.

## 3 Tamper-proof profile cylinder

The anti-picking system prevents manipulation by objects inserted into the lock. The profile cylinder drill-proofing gives you a sense of extra security. The emergency and hazard function is convenient: the door can still be opened and closed when the key is inserted on the inside. A tamper-proof locking cylinder certified in accordance with DIN 18252 / DIN EN 1303 is supplied including 5 reversible keys and 2 key caps.

## Flush-mounted security rose escutcheon on exterior


The flush-fitting stainless steel security rose escutcheon fits into the door leaf particularly elegantly, and also protects the profile cylinder against being drilled open. Please contact your Hörmann dealer if you wish to use your own cylinder systems.

## 3 Aluminium interior lever

ThermoPlan Hybrid entrance doors are equipped as standard with the attractive Rondo interior lever, stove-enamelled in white. Optionally, it is also available in stainless steel or RAL to choose as well as the versions Caro or Okto, also in stainless steel.

## 5 Stainless steel lock plate

The lock plate is optimally adjusted by the Hörmann specialist partner so that your door falls shut optimally and can be securely locked.



**6 5-point security lock H5 and security bolts on the hinge side**

When locking, 3 steel swing bolts with 2 additional bolt locks pivot into the stainless steel lock plate. The swing bolts make it more difficult for the door to be pulled apart or forced open.

**7 Electronic spyhole (optional)**

Your entrance area is monitored with a wide angle camera. The spyhole with 3.5" LCD monitor is ideal for small children and persons who depend on a wheelchair.

**Integrated overhead door closer (optional, not shown)**

The integrated, invisible overhead door closer closes the door and gives it an elegant interior view – especially in combination with concealed hinges.

**Opening limiter (optional, not shown)**

The high-quality opening limiter in the metal version restricts the door opening to an opening angle of 105°. It is individually adjustable and features the convenient soft stop function.





## Thermal insulation world champion with high-tech equipment

Our aim was to create an entrance door that exceeds your requirements for security, thermal insulation, technical equipment and design. We have succeeded with the high-tech ThermoCarbon entrance door. With  $U_D$ -values of up to approx.  $0.47 \text{ W}/(\text{m}^2 \cdot \text{K})$ , the ThermoCarbon is a deserving thermal insulation world champion and, with the optional RC 4 equipment, is also a frontrunner in terms of security. With its high-tech leaf profile made of carbon glass-fibre hybrid material, our premium entrance door is exceptionally impressive, offering a high degree of rigidity and impact resistance as well as improved acoustic insulation like none other.

The ThermoCarbon entrance door is available in 20 modern door styles and 19 preferred colours, and optionally in two colours on request. Of course, you can customise your entrance door even further with many other equipment options such as handles, glazings and lock variants.

---

ThermoCarbon  
from €4400\*

---

\* Recommended retail price



# Construction

- 1 100 mm aluminium door leaf with PU rigid foam infill and internal leaf profile
- 2 Thermal break and high stability thanks to carbon glass-fibre reinforced composite leaf profile
- 3 111 mm aluminium door frame with thermal break
- 4 Triple sealing with two all-round seals

Fulfils all requirements of the energy saving regulation and is certified for low-energy houses by the ift Rosenheim\*

Suitable for fitting without thermal bridges

**Thermal insulation:  $U_D$ -value of up to approx.  $0.47 \text{ W}/(\text{m}^2 \cdot \text{K})^{**}$**

**Acoustic insulation:  $R_{w,p}$  up to 34 dB**



The complete performance characteristics can be found on page 94.



As standard



Optional



## Equipment

- 5 Solid door view from the inside, as standard in Traffic white RAL 9016, matt, like on residential internal doors
  - 6 Concealed hinges incl. adjustable opening limiter with soft stop
  - 7 Stainless steel lever handle
  - 8 Quadruple-pane thermal insulation glazing with safety glass on both sides
  - 9 Profile cylinder protected against manipulation
- 
- 10 RC 3 security equipment\*\*\* with 9-point security lock
- 

Optional RC 4 security equipment

---

## Colour

- As standard in Traffic white, RAL 9016, matt
- Optionally in 19 preferred colours
- Optionally in RAL to choose

For further information, see page 84.

## Interior view




\* Not style 310

\*\* Dependent on door size. Specified values for RAM 1230 x 2180 mm

\*\*\*Break-in-resistant components are only effective in preventing burglaries when closed and locked, with the key removed.





**Style 189**

Preferred colour  
White aluminium RAL 9006,  
silk-gloss, stainless steel  
handle HOE 615,  
matt float design glass  
with 7 clear stripes



**Style 504**

Standard colour Traffic white  
RAL 9016, matt, stainless  
steel handle HOE 500,  
matt float design glass  
with 5 clear stripes



**Style 680**

Preferred colour Slate grey  
RAL 7015, matt, stainless  
steel handle HOE 700,  
Pave white ornamental  
glass



**Style 862**

Standard colour Traffic white  
RAL 9016, matt, stainless  
steel handle HOE 620



**Style 650**

Preferred colour Cream  
RAL 9001, fine structure  
matt, stainless steel handle  
HOE 700, Pave white  
ornamental glass



**Style 686**

Preferred colour Window  
grey RAL 7040, matt,  
stainless steel handle  
HOE 610, matt float design  
glass with 7 clear stripes

◀ **ThermoCarbon style 680** in preferred colour Slate grey RAL 7015, fine structure matt, with side elements





**Style 565**

Standard colour Traffic white RAL 9016, matt, design handle G 760 in Hörmann colour CH 703 Anthracite, fine structure matt, side elements with matt float ornamental glass



**Style 568**

Preferred Hörmann colour CH 607 Chestnut, fine structure matt, design handle G 750 in anodised aluminium E6 / EV 1



**Style 300**

Standard colour Traffic white RAL 9016, matt, handle bar in White aluminium RAL 9006, silk-gloss, side elements with matt float ornamental glass



**Style 301**

Preferred colour Anthracite grey RAL 7016, matt, flush-fitting aluminium embellishment and handle bar in White aluminium RAL 9006





**Style 306**

Standard colour Traffic white RAL 9016, matt, recessed grip in Traffic white RAL 9016, matt, flush-fitting stainless steel handle, matt float ornamental glass



**Style 314**

Standard colour Traffic white RAL 9016, matt, recessed grip in Traffic white RAL 9016, matt, flush-fitting stainless steel handle, matt float ornamental glass



**Style 310**

Preferred Hörmann colour CH 607 Chestnut, fine structure matt, flush-fitting stainless steel handle, matt float ornamental glass



**Style 312**

Standard colour Traffic white RAL 9016, matt, flush-fitting handle bar in White aluminium RAL 9006, silk-gloss, matt float design glass with a clear, vertical stripe



**Style 302**

Preferred colour Stone grey RAL 7030, matt, flush-fitting handle bar in White aluminium RAL 9006, silk-gloss, matt float design glass with a clear, vertical stripe, side elements with matt float ornamental glass

# Functionality meets aesthetics



## **Style 823 ■ NEW**

Preferred colour Anthracite grey RAL 7016, matt, optionally with LED spotlight in handle, handle profile in White aluminium RAL 9006, fixing profiles in door colour



# Room-high door for spacious entrance portal



XXL version up to  
3000 mm shown



## Style 860

Preferred colour Ruby red RAL 3003, matt, optionally with stainless steel handle HOE 710, side elements with matt float ornamental glass



**Style 308**

Standard colour Traffic white RAL 9016, matt, handle bar and recessed grip in Anthracite grey RAL 7016, matt, side elements with matt float ornamental glass



**Style 309**

Preferred colour Slate grey RAL 7015, fine structure matt, flush-fitting handle bar in White aluminium RAL 9006, silk-gloss



**Style 305**

In Hörmann preferred colour CH 703 Anthracite, fine structure matt, aluminium embellishment in Ruby red RAL 3003, matt, flush-fitting stainless steel handle, side elements with matt float ornamental glass



**Style 304**

Preferred colour White aluminium RAL 9006, silk-gloss, recessed grip in White aluminium RAL 9006, silk-gloss, flush-fitting stainless steel handle

# Premium down to the last detail

## 1 Concealed hinges

The hinges of the ThermoCarbon entrance door are concealed between the door frame and leaf, i.e. they are not visible either from inside or outside; this is an elegant solution for your home. The door leaf can be simply and easily adjusted by the Hörmann specialist partner. This way, you can close your entrance door comfortably and securely at all times.

## 2 Profile cylinder protected against manipulation

The tamper-proof profile cylinder, certified in accordance with DIN 18252 / DIN EN 1303, impresses with premium fittings: an anti-picking system, which prevents manipulation by objects inserted into the lock, drill-proofing and an emergency and hazard function. This means that the door lock can still be opened when a key is inserted on the inside. 5 reversible keys and 2 key caps are delivered with the door.

## Flush-mounted security rose escutcheon on exterior


The flush-fitting stainless steel security rose escutcheon fits into the door leaf particularly elegantly, and also protects the profile cylinder against being drilled open. Please contact your Hörmann dealer if you wish to use your own cylinder systems.

## 3 Stainless steel interior lever

The elegant stainless steel interior lever Caro is used as standard for entrance doors ThermoCarbon.

## 4 Stainless steel lock plate

The high-quality stainless steel lock plate is elegantly integrated into the door frame and can be very easily adjusted by the Hörmann specialist partner. This allows for secure locking of the door at all times.



**5 9-point security lock H9 and concealed hinges that cannot be forced open**

The ThermoCarbon is equipped with 9-point security. When locking, 5 steel swing bolts and 4 bolt locks pivot into the stainless steel lock plate. This top quality security solution protects your door with just one turn of a key. XXL doors are supplied with the S7 automatic lock with 7-point locking as standard.

## Flush-fitting exterior handles for exclusive door designs

**6 Stainless steel handle with recessed grip**

Doors with a stainless steel handle come with a recessed grip in the colour of the door as standard.

**Individual handle colours**

All flush-fitting exterior handles (except for stainless steel handles) are also available in several colour variants (see page 89 for more information).

**7 Continuous aluminium handle bar**

As standard, the complete handle bar is supplied in White aluminium, RAL 9006, silk-gloss, with a recessed grip in the colour of the door.

**8 Aluminium handle bar with recessed grip**

As standard, this handle bar comes in White aluminium, RAL 9006, silk-gloss, with a recessed grip in the colour of the door.







## Glass entrance doors for well-lit entrance areas

Our TopComfort glass entrance doors create a bright and cheerful entrance area with solid equipment. The doors are characterised by an 80-mm-thick aluminium door profile and 80-mm aluminium door frame with thermal break and feature good thermal insulation with a  $U_D$ -value up to  $1.3 \text{ W}/(\text{m}^2 \cdot \text{K})$ . The standard 5-point security lock provides the security you expect of an entrance door. This way, you can design an entrance area that is not only tasteful, but also secure.

You can choose between 9 exclusive glass door styles that let in a maximum of natural light. We can supply the frame in one of 19 preferred colours according to your preferences. You can customise the door of your choice with stylish exterior and interior handles and glazings.

---

TopComfort  
from €3200\*

---

# Construction

- 1** Aluminium leaf profile with thermal break, optionally with additional thermal insulation
- 2** 80 mm aluminium door frame with thermal break
- 3** Double sealing
- 4** Triple thermal insulation glass with 8 mm safety glass on interior and exterior, optionally as double thermal insulation glass

---

Fulfils all requirements of the energy saving regulation

---

Suitable for fitting without thermal bridges

---



**Thermal insulation:  $U_D$ -value of up to approx.  $1.3 \text{ W}/(\text{m}^2 \cdot \text{K})^*$**

---

**Acoustic insulation:  $R_{w,p}$  up to 39 dB**

---

The complete performance characteristics can be found on page 94.



# Equipment

- 5 Square glazing beads, with butt joints
- 6 3-way adjustable hinges
- 7 Aluminium interior lever
- 8 Triple thermal insulation glazing
- 9 Profile cylinder protected against manipulation
- 10 5-point security lock

---

**Optional RC 2 / RC 3 security equipment\*\***

---

# Colour

- As standard in Traffic white, RAL 9016, matt
- Optionally in 19 preferred colours
- Optionally in RAL to choose

For further information, see page 84.

# Interior view



\* Dependent on door size. Specified values for RAM 1230 x 2180 mm

\*\* Break-in-resistant components are only effective in preventing burglaries when closed and locked, with the key removed.



**Style 100**

Standard colour Traffic white RAL 9016, matt,  
stainless steel handle 38-1,  
Master-Carré ornamental glass



**Style 101**

Standard colour  
Traffic white RAL 9016,  
matt, stainless steel  
handle 38-1, Master-Carré  
ornamental glass



**Style 100 MG 111**


Preferred colour Hörmann CH 703 Anthracite,  
fine structure, matt, stainless steel handle 38-2,  
design glass with matt stripes



**Style 100 MG 112**

Standard colour Traffic  
white RAL 9016, matt,  
stainless steel handle 38-2,  
Micrograin design glass  
with horizontal structure





**Style 100 MG 113**

Traffic white RAL 9016, matt, stainless steel handle 38-2, door and side elements with design glass with 25 matt stripes



**Style 100 MG 114**

Preferred colour White aluminium RAL 9006, silk-gloss, stainless steel handle 38-2, matt design glass with clear semi-circles and stripes




**Style 100 MG 115**

Standard colour Traffic white RAL 9016, matt, stainless steel handle 38-2, design glass matt with rectangles



**Style 100 MG 116**

Preferred colour Anthracite grey RAL 7016, matt, stainless steel handle 38-2, design glass with matt stripes and crescent



**Style 100 MG 117**

Preferred colour Grey aluminium RAL 9007, fine structure matt, stainless steel handle 38-2, matt design glass with 9 clear stripes




## Door that make you feel at home

Our optional extras offer you a wide range of possibilities to design the door of your dreams according to your individual preferences. For example, you can combine colours, handles and glazings based on your individual style. We also offer you a variety of security options: You can choose between different automatic locks and convenient operating options that fulfil your needs. Whatever you decide on – at Hörmann, you will find an entrance door to suit both your taste and your home.

## Designing entrances with side elements and transom lights

To create an impressive entrance to your home, you can individually combine each of the illustrated ThermoSafe, ThermoSafe Hybrid, ThermoPlan Hybrid and TopComfort entrance doors with side elements and transom lights, or combine each ThermoCarbon entrance door with side elements. For an elegant and attractive overall look that will stand the test of time.



Entrance door with two side elements and transom light



Entrance door with one side element



Entrance door with one side element, style infill in the side element




Entrance door with transom light

The illustrations show ThermoSafe entrance doors with side elements and transom lights in vertical / horizontal profile construction

# Side elements with practical letter box systems

Hörmann can provide you with the letter box system based on your needs and the number of flats. Letter box systems and letter drops are available with bell buttons, light switches and intercom mesh, all with high-grade stainless steel fascia and insulated aluminium panel infill plate for simple fitting without extensive brickworks.



Letter box system Leabox for 1 flat ■ NEW



Letter box system RSA 2, insulated, for 5 flats

Door version	ThermoSafe Hybrid / ThermoSafe	ThermoPlan Hybrid	ThermoCarbon	TopComfort
Side elements	●	●	●	●
Side elements with style infills		●		
Transom lights	●	●		●
Letter box systems	●	●		●



# Find your favourite colour

At Hörmann, we value individuality and variety. That's why we offer entrance doors in the colour of your choice as a matter of course. For example, you can select your favourite colour from the particularly inexpensive Traffic white RAL 9016 and additional preferred colours. Your Hörmann dealer will be happy to assist you.




**Please note:**

All colours are based on RAL. All colours for ThermoSafe, ThermoSafe Hybrid, ThermoPlan Hybrid, ThermoCarbon and TopComfort are supplied with a matt powder-coating (except RAL 9006, silk-gloss and RAL 9016, high-gloss). Dark colours should not be used for doors that are exposed to the sun.

The colours and surfaces shown are subject to the limitations of the printing process and cannot be regarded as binding. Please consult with your local Hörmann specialised dealer.

## Standard and preferred colours



- 1 RAL 9016 Traffic white (standard)
- 2 RAL 9016 Traffic white (high-gloss)
- 3 RAL 9006 White aluminium (silk-gloss)
- 4 RAL 8028 Terra brown
- 5 RAL 7040 Window grey
- 6 RAL 7035 Light grey
- 7 RAL 7030 Stone grey
- 8 RAL 7016 Anthracite grey
- 9 RAL 7015 Slate grey
- 10 RAL 6009 Fir green
- 11 RAL 6005 Moss green
- 12 RAL 3003 Ruby red

## Textured colours



- 1 RAL 9007 Grey aluminium, fine structure matt
- 2 RAL 9001 Cream, fine structure matt
- 3 RAL 7039 Quartz grey, fine structure matt
- 4 RAL 7030 Stone grey, fine structure matt
- 5 RAL 7016 Anthracite grey, fine structure matt
- 6 RAL 7015 Slate grey, fine structure matt
- 7 Hörmann colour CH 703 Anthracite, fine structure matt
- 8 Hörmann colour CH 607 Chestnut, fine structure matt

# Custom glazings for side elements and transom lights

Each glass type has a different look depending on colour, structure and finish. You can thus match your entrance door, side elements and transom lights according to your wishes with custom glazings or design glass.



Float, clear / clear glass



Float matt / sand-blasted



Satinato



Pave white



Parsol grey



Parsol grey, matt



Ornament 504



Ornament 553



Chinchilla



Micrograin (Madras basic)



Reflo, clear



Reflo, matt



Silk



Master-Carré



Baroque white ■ NEW



Niagara white ■ NEW



Gothic white ■ NEW



Cathedral white ■ NEW




Cast antique white ■ NEW




Uadi white ■ NEW

# Tangibly beautiful design

Each Hörmann entrance door is delivered as standard with the handle shown in the product photos. However, on request, you can equip many of our doors with a customised handle.





+ mm + = axis dimension  
 H mm H = handle length

All details in mm

## Attractive lever handles

Every Hörmann entrance door is equipped with an elegant interior lever. The different lever handle sets, lever / knob and security lever handle sets are optionally available based on design, comfort or safety according to your wishes.



Aluminium lever handle Rondo  
In Traffic white, matt, RAL 9016  
as standard for ThermoPlan Hybrid,  
ThermoSafe Hybrid, ThermoSafe  
and TopComfort



Stainless steel lever handle Caro  
As standard for ThermoCarbon and  
optionally for ThermoPlan Hybrid,  
ThermoSafe Hybrid and  
ThermoSafe



Aluminium security handle set 62-1,  
optionally for ThermoPlan Hybrid, ThermoSafe Hybrid  
and ThermoSafe



Stainless steel lever handle Okto  
Optionally for ThermoPlan Hybrid,  
ThermoSafe Hybrid and ThermoSafe



Stainless steel lever handle set  
Type D-116 optionally for  
ThermoPlan Hybrid, ThermoSafe  
Hybrid and ThermoSafe



Stainless steel lever handle set  
Type D-335, optionally for  
ThermoPlan Hybrid, ThermoSafe  
Hybrid and ThermoSafe



Stainless steel security handle set 62-4 in Traffic white, matt,  
RAL 9016, optionally for ThermoPlan Hybrid,  
ThermoSafe Hybrid and ThermoSafe



# Individual colour combinations

For the exclusive ThermoCarbon entrance door styles 300, 301, 302, 304, 305, 308 and 312, you have the option to individually coordinate the flush-fitting handle bar and recessed grip with the colour of your entrance door or embellishment.



**Style 300**  
In Traffic white RAL 9016, matt, handle bar in Traffic white RAL 9016, matt, recessed grip in door colour



**Style 300**  
In the preferred colour Slate grey, RAL 7015, matt, handle bar in White aluminium RAL 9006, silk-gloss, recessed grip in the preferred colour White aluminium RAL 9006, silk-gloss



**Style 301**  
In Hörmann preferred colour CH 703 Anthracite, fine structure matt, aluminium embellishment in preferred colour Ruby red RAL 3003, matt, handle bar in preferred colour Ruby red RAL 3003, matt, recessed grip in door colour

## Design handle G 750




Delivered as standard in E6 / EV 1, with stainless steel end caps



No surcharge for the door surface colour, with stainless steel end caps



Optionally available in preferred colour (shown in Ruby red RAL 3003, matt) or RAL to choose deviating from door surface colour, with stainless steel end caps



### Effective illumination with LED light strip

The design handle G 750 and the DesignPlus handle G 760 are also optionally available with a light strip integrated into the handle. This particularly emphasizes your ThermoSafe or ThermoSafe Hybrid entrance door at night.

## DesignPlus handle G 760



Handle bar in anodised aluminium E6 / EV 1 as standard, with stainless steel end caps (shown: handle embellishment in Hörmann colour CH 703, matt textured Anthracite)



Handle embellishment in anodised aluminium E6 / EV 1 as standard (handle bar in anodised aluminium E6 / EV 1)

### Handle embellishments are also available in timber designs



Decograin Light Oak



Decograin Golden Oak



Decograin Dark Oak



Decograin Night Oak



Decograin Rosewood

## Securing excellent properties

Fingerprint, code or radio – Hörmann offers automatic lock variants for more security and convenient operation. ThermoSafe, ThermoSafe Hybrid and ThermoPlan Hybrid entrance doors are optionally available at no surcharge with the S5 automatic lock that automatically and securely locks your entrance door at four different points as soon as the door falls shut. You can also equip your **ThermoCarbon entrance door** with the 7-point S7 automatic lock at no surcharge. You may, of course, also continue to use a key to lock and unlock your door.



The elegant electro duct for concealed hinges guides the cable from the door leaf directly into the frame. This way there is no rebate air gap between the frame and leaf.

## S5 / S7 automatic lock

The **bolt lock with mechanical self-locking** is available **optionally without a surcharge**. When the door falls shut, the bolts automatically extend and securely lock the entrance door. In addition, the door can also be secured via the lock with another bolt, e.g. if you are away on holiday.

## Automatic lock S5 / S7 Comfort

**In addition to automatic self-locking**, the automatic lock S5 / S7 Comfort is also **equipped with an electric motor** that unlocks the bolts of your entrance door with an electric impulse. For this purpose, the S5 / S7 Comfort is prepared for **connection to a button on an existing home intercom**. This way, you can conveniently open your entrance door at the press of a button, for example from an upper storey. **If you want to open your entrance door conveniently from the outside**, you can choose from the lock variants Code, Scan, Smart or Bluetooth (see the following pages).

## S5 / S7 Code automatic lock

Very convenient: With the automatic lock, simply entering your personal security code opens your entrance door from the outside. You can save up to 20 different codes.



Barrier-free entrances



S5 / S7 Comfort – open the door at the push of a button



S5 / S7 Code – door is opened by entering a code – fitted in the door leaf (dimensions 45 x 75 mm)



Code switch – fitted in the door handle (dimensions 45 x 75 mm)



Elegant code switch with touch-sensitive touch surface (optional for ThermoSafe and ThermoSafe Hybrid entrance doors) (dimensions 56 x 102 mm)

## S5 / S7 Scan automatic lock

Open your entrance door with your fingerprint. The almost flush-fitting finger-scan\* integrated into the door leaf or handle recognises up to 150 fingerprints and is VDS-approved. Furthermore, you can control another device such as the exterior lighting or your garage door operator in addition to the entrance door lock.



## S5 / S7 Smart automatic lock

You can conveniently open your entrance door with an optional hand transmitter or a radio switch. The extremely secure radio system ensures that no unauthorised person can copy your radio signal. Another advantage is that you can use the same hand transmitter to operate your Hörmann garage door or entrance gate. The S5 / S7 Smart remote control can also be installed as part of the S5 / S7 Scan and S5 Code convenience packages.

## Automatic lock S5 / S7 Bluetooth

Opening and closing your door via Bluetooth using your smartphone is even more convenient. Lock and unlock your entrance door using the user-friendly Hörmann **BlueSecur app**. In addition, other user permissions\*\* can be permanently or temporarily transferred to other smartphones, so that every family member always has their “entrance door opener” with them.



S5 / S7 Scan – door is opened by fingerprint – fitted in the door leaf (dimensions 35 × 66 mm)



Finger-scan in the door handle (dimensions 35 × 66 mm)



S5 / S7 Smart – door is opened using BiSecur radio



Simple smartphone operation of the automatic lock using the Hörmann BlueSecur app

\* Changing fingerprint characteristics in children, adolescents and the elderly can cause malfunctions. For temperature ranges from -20°C to +80°C.

\*\* In-app purchases may be required

## Opening aid ECTurn

ThermoCarbon, ThermoSafe Hybrid and ThermoSafe entrance doors can now be optionally equipped with the ECTurn. The opening aid is integrated elegantly into the door leaf and frame or available as a surface-mounted version. With the automatic lock and ECTurn, you can automatically open and close your door. Due to low energy operation, the opening aid requires no safety devices. The force of the ECTurn is adapted to the leaf, minimising potential hazards for persons.



Convenient opening with the ECTurn opening aid. The opening aid is also available elegantly integrated into the door leaf and frame.

## Door operator HDO 200

**Door operator HDO 200**, optional for all aluminium entrance doors TopComfort, **in combination with a door version without threshold** incl. retractable bottom seal, is the ideal **solution for barrier-free entrances**. The inconspicuous Flatscan sensor monitors the area of travel and ensures safe operation. The operator can be conveniently operated via buttons, radar / movement detectors, etc., and optionally with BiSecur radio technology with all Hörmann hand transmitters, radio control elements, radio internal push buttons or the BiSecur app. All door parameters such as the opening or closing speed can be individually adjusted. Thanks to speed control, the operator not only operates safely in terms of opening and closing speed, but is also pleasantly quiet.



Barrier-free entrances



For barrier-free entrances in combination with a door version without threshold: the door operator HDO 200



Select your hand transmitter or radio switch from our broad accessories programme. More information can be found in the "Garage door and entrance gate operators" brochure.



# Performance characteristics

Our entrance doors offer reliable functional safety and approved performance characteristics. This allows you to enjoy your Hörmann entrance door for years to come.



## Performance characteristics

	ThermoSafe	ThermoSafe Hybrid	ThermoPlan Hybrid	ThermoCarbon	TopComfort
Operating forces EN 12217	Up to class 5	Up to class 5	Up to class 5	Up to class 3	Up to class 3
Long-term functionality / mechanical load EN 12400	Up to class 5	Up to class 5	Up to class 5	Up to class 6	Up to class 5
Differential climate behaviour EN 12219	Up to 2d / 2e	Up to 2d / 2e	Up to 2d / 2e	Up to 2d / 2e	Up to 2d / 2e
Air permeability EN 12207	Up to class 4	Up to class 4	Up to class 4	Up to class 4	Up to class 3
Water tightness under heavy rain EN 12208	Up to class 8A	Up to class 8A	Up to class 8A	Up to class 7A	Up to class 5A
Resistance to wind load EN 12210	Up to class C2 / B2	Up to class C2 / B2	Up to class C2 / B2	Up to class C2 / B2	Up to class C32
Impact resistance EN 13049	Up to class 2	Up to class 2	Up to class 5	Up to class 3	Up to class 3
Mechanical strength EN 1192	Up to class 3	Up to class 3	Up to class 3	Up to class 3	Up to class 1
Thermal insulation	Up to 0.87 W/(m <sup>2</sup> ·K)	Up to 0.87 W/(m <sup>2</sup> ·K)	Up to 0.78 W/(m <sup>2</sup> ·K)	Up to 0.47 W/(m <sup>2</sup> ·K)	Up to 1.3 W/(m <sup>2</sup> ·K)
Acoustic insulation	Up to 34 dB	Up to 36 dB	Up to 36 dB	Up to 35 dB	Up to 39 dB
Burglar protection EN 1627 (optional)	RC 3	RC 3, RC 4 (optional)	RC 3	RC 3, RC 4 (optional)	RC 2, RC 3 (optional)

**Note:** The specified performance characteristics indicate the maximum possible performance of the entrance door. This performance may vary according to the equipment of the entrance door.

# SIZES AND FITTING DATA

## ThermoSafe / ThermoSafe Hybrid entrance door sizes

70 mm frame version	Overall frame dimension* (ordering size)	Structural opening*	Clear frame dimension
Standard	Max. 1250 x 2250	Max. 1270 x 2260	Max. 1110 x 2180
Oversize	Max. 1250 x 2350	Max. 1270 x 2360	Max. 1110 x 2280
XXL	Max. 1250 x 2500	Max. 1270 x 2510	Max. 1110 x 2430

## ThermoSafe / ThermoSafe Hybrid side element sizes


Vertical profile construction	Side element height*	TM side element width*	TM entrance door width*
1-sided	Max. 3000	260 – 1600	Max. 1230
2-sided	Max. 3000	260 – 1600	Max. 1210

The max. transport size of a door assembly (incl. side elements, transom lights and surface-mounted profiles) must not exceed 2700 mm on any side.

Coupling construction	Side element height*	TM side element width*	TM entrance door width*
1- / 2-sided	Max. 3000	300 – 2500**	1250


\* For 110 mm frames + 40 mm

\*\* With Reflo or Micrograin glazing




## ThermoSafe / ThermoSafe Hybrid

### Bottom spacer profile / transport protection




For vertical profile constructions with inserted, continuous tubular supports (shown on right).

### Horizontal view of door



### Vertical view of door



All dimensions in mm

# SIZES AND FITTING DATA

## ThermoPlan Hybrid entrance door sizes

70 mm frame version	Overall frame dimension* (ordering size)	Structural opening*	Clear frame dimension
Standard	Max. 1250 x 2250	Max. 1270 x 2260	Max. 1110 x 2180
Oversize	Max. 1250 x 2350	Max. 1270 x 2360	Max. 1110 x 2280
XXL	Max. 1250 x 2500	Max. 1270 x 2510	Max. 1110 x 2430

## ThermoPlan Hybrid side element sizes

Vertical profile construction	Side element height*	TM side element width*	TM entrance door width*
1-sided	Max. 3000	260 – 1600	Max. 1230
2-sided	Max. 3000	260 – 1600	Max. 1210

The max. transport size of a door assembly (incl. side elements, transom lights and surface-mounted profiles) must not exceed 2700 mm on any side.



Coupling construction	Side element height*	TM side element width*	TM entrance door width*
1- / 2-sided	Max. 3000	300 – 2500**	1250

\* For 110 mm frames + 40 mm

\*\* With Reflo or Micrograin


## ThermoPlan Hybrid

### Bottom spacer profile / transport protection





For vertical profile constructions with inserted, continuous tubular supports (shown on right).

### Horizontal view of door



### Vertical view of door



## ThermoCarbon entrance door dimensions


Version	Overall frame dimension (ordering size)	Structural opening	Clear frame dimension
Standard	max. 1340 × 2350	Max. 1360 × 2360	Max. 1140 × 2230
XXL	Max. 1340 × 3000	Max. 1360 × 3010	Max. 1140 × 2880

## ThermoCarbon side element dimensions

Vertical profile construction	Side element height	TM side element width	TM entrance door width
1-sided	Max. 3000	300 – 1600	Max. 1300
2-sided	Max. 3000	300 – 1600	Max. 1260


The max. transport size of a door assembly (incl. side elements, transom lights and surface-mounted profiles) must not exceed 2700 mm on any side.

Coupling construction	Side element height	TM side element width	TM entrance door width
1- / 2-sided	Max. 3000	340 – 1600	1340




## ThermoCarbon

### Bottom spacer profile / transport protection




For vertical profile constructions with inserted, continuous tubular supports (shown on right).

### Horizontal view of door



### Vertical view of door



All dimensions in mm

# SIZES AND FITTING DATA

## TopComfort entrance door sizes


70 mm frame version	Overall frame dimension* (ordering size)	Structural opening*	Clear frame dimension
Standard	Max. 1300 x 2500	Max. 1270 x 2510	Max. 1160 x 2430

## TopComfort side element sizes

Vertical profile construction	Side element height*	TM side element width*	TM entrance door width*
1-sided	Max. 3000	260 – 1600	Max. 1230
2-sided	Max. 3000	260 – 1600	Max. 1210


The max. transport size of a door assembly (incl. side elements, transom lights and surface-mounted profiles) must not exceed 2700 mm on any side.

Coupling construction	Side element height*	TM side element width*	TM entrance door width*
1- / 2-sided	Max. 3000	300 – 1600	1250




## TopComfort

### Bottom spacer profile




For vertical profile constructions with inserted, continuous tubular supports (shown on right).

### Horizontal view of door



\* Optional frame width

### Vertical view of door





# Experience Hörmann quality in new construction and modernisation

Hörmann provides an excellent basis for comprehensive planning. Carefully matched solutions offer you the very best in perfectly designed products for every area.

- **Garage doors**

Optimally match your personal architectural style: up-and-over or sectional doors made of steel or timber.

- **Gate and door operators**

Enjoy extra convenience and break-in-resistant security with Hörmann operators for garage doors and entrance gates. You can profit from the convenience of Hörmann door operators in your residential space as well.

- **Entrance doors**

Our comprehensive entrance door ranges include models that fit almost every need and requirement.

- **Residential internal doors**

Our high-quality timber and glass doors give your home an extra level of comfort and integrate harmoniously into the overall appearance of your home.

- **Steel doors**

Sturdy doors for your entire home, from basement to roof.

- **Frames**

Choose from our comprehensive range of products for new construction, expansion and modernisation.



Garage doors and entrance gate operators



Residential internal doors and door operators



Steel doors