


Hörmann ProMatic Akku Garage Door Operator

All the advantages of Hörmann's rail-guided garage door operator now also for garages without electricity



Compact dimensions Easy transport



Power for up to 40 days Easy overnight recharging



Boom-guided operation Patented door latching



The solution for prefabricated garages and blocks of garages without electricity



Operating comfort without mains connection

Just press a button to open the garage, even without mains connection in your garage. With ProMatic Akku you have your power source in the direct vicinity of the drive unit. Enjoy the operating comfort without the need to recharge the accumulator for up to 40 days.

Easy accumulator recharge

Shortly before the accumulator gets discharged, an audible signal will be given. Similar to the recharging of a cellular phone, you just have to connect the accumulator to a power outlet via the charging unit which is included in the scope of supply. The accumulator will be fully recharged overnight and your door drive is ready for operation again. A spare accumulator is available optionally.

Comfortable recharging by a solar module

No manual recharging of the accumulator is required when using the optional solar module which can be easily mounted at or on the garage.

Suitable for up-and-over and sectional doors

The ProMatic Akku garage door operator fits all standard up-and-over and sectional doors - all makes, old and new.







* For warranty conditions, specifications and further information about Hörmann's garage door operators see www.hoermann.com

ProMatic Akku garage door operator



Suitability

For garage doors with a door leaf size of up to 8 m² or a width of 3000 mm.
Pull and push force: 350 Nm

Accumulator

Capacity: approx. 40 days** Charging time: 5 - 10 h*** Weight: 8.8 kg Dimensions:

330 x 220 x 115 mm

Scope of supply

Drive unit

Dual-button hand transmitter Accumulator with charging unit 5 m cable

Accumulator bracket, fitting material



Solar module **NEW**

Optional
Including connecting
hardware, 10 m cable and
charge controller
Dimensions: 300 x 400 mm

* based on 4 cycles per day and an ambient temperature of 20°C

*** depending on the charging condition



Flexible fitting

Using the 5 m cable, you may place the accumulator almost anywhere in your garage, either mounted on the wall, on the floor or directly at the door's guide rail. The accumulator comes with a special holding bracket and all connecting hardware.

Should your garage not have a second access door, then an external emergency release must be provided.

If you need professional advice - contact us!