## Garage Door Operators

Safe Automatic Force Adjustment Only 2.0 Watts Stand-By Consumption Convenience at Affordable Price 5 Year Manufacturer's Warranty\*

\*subject to terms and conditions



0800 525 442

Garage Door Operators







Two MIDI-handsets hipped as standard



One wall holder is supplied as standard



The optional MINI-handset compared to the standard MIDI-hand transmitter





Replacement components, i.e. Printed Circuit Boards, Transformers etc. are easily exchanged and widely available. In the unlikely event of failure, with Seip there is no need to purchase a costly motor head

The Digi-Pad - a highly convenient extra.

## Why SEIP should be your Automatic Choice

The TM series offers only quality components: powerful motors with self locking gears and electronics designed and manufactured in Germany. We are one of few manufacturers using quality galvanized steel with a thickness of 2.5 mm to assure the highest mechanical strength.

The compact design of the TM series is highly efficient and space saving.

We have confidence in our products, backed up by our five year manufacturer's warranty. In support of this claim, our products are running on permanent test. On our test stands, operators run 24 hours a day, 365 days of the year to check and prove the strength and reliability of components. Under stringent test conditions, we reach a minimum of 60,000 cycles, moving weights up to 100 kg.

And finally, SEIP UK LTD prides itself not only on its superb range of quality products, but with providing all customers with a back up service second to none!



The robust standard handset can conveniently be attached to a key-ring by means of the sturdy metal ring-holder



Our door operators are being tested for safety standards in our factory testing stands with different types and sizes of garage doors.





2	Technical Data	ТМ 80
	Pulling Force	80 kg
	Max. Peak Pulling Force	95 kg
	For Door Weights up to	< 200 kg
	At a Door Size of	< 15 m <sup>2</sup>
	Max. Running Speed	14 cm/sec.
	Time for opening of 2,10m at Vmax. *	18 sec.
	Integrated Lighting	230V AC, max. 40 Watt
	Lighting Duration adjustable	30 sec. to 10 min.
	Lighting to be switched on seperately	ja
	Automatic Closing**	3 Pre-Set times available
	Blinking Pre-Warning Light	adjustable
	Max. Number of Remotes	10
	Power Consumption in Stand-By	2.0 Watt
	Power Supply	190-250V AC
	Net Running Length	2,500 mm
	Overall Length	3,150 mm
	*on a neutral garage door with a weight of 90kg max.	Subject to technical alterations!

\*\*Photo-Cell as optional extra required